

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/021521

International filing date: 02 July 2004 (02.07.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/570,666
Filing date: 13 May 2004 (13.05.2004)

Date of receipt at the International Bureau: 13 September 2004 (13.09.2004)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1216252

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE


United States Patent and Trademark Office

September 08, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/570,666
FILING DATE: *May 13, 2004*

Certified by



Jon W Dudas

Acting Under Secretary of Commerce
for Intellectual Property
and Acting Director of the U.S.
Patent and Trademark Office



22783 U.S. PTO

Express Mail No. EV238420820US

PROVISIONAL APPLICATION COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION under 37 C.F.R. 1.53 (c).

			Docket Number	COR21 PP306A
INVENTOR(s)/APPLICANT(s)				
LAST NAME	FIRST NAME	MIDDLE INITIAL	RESIDENCE (CITY AND EITHER STATE OR FOREIGN COUNTRY)	
Marcolux	Michael		Wyoming, Michigan	
Johnson	David	R.	Granger, Indiana	
TITLE OF THE INVENTION (280 characters max)				
WOUND DRESSING, INGREDIENT DELIVERY DEVICE AND IV HOLD-DOWN, AND METHOD RELATING TO SAME				
CORRESPONDENCE ADDRESS				
Customer No. 000,277				
STATE		ZIP CODE		COUNTRY
ENCLOSED APPLICATION PARTS (check all that apply)				
<input checked="" type="checkbox"/> Specification Number of Pages <u>31</u> <input type="checkbox"/> Small Entry Statement <input checked="" type="checkbox"/> Drawings Number of Sheets <u>5</u> <input checked="" type="checkbox"/> Other (specify) <u>X</u> Return Postcard				
METHOD OF PAYMENT (check one)				
<input checked="" type="checkbox"/> A check or money order is enclosed to cover the Provisional filing fees <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees and credit Deposit Account Number: <u>16-2463</u>			PROVISIONAL FILING FEE AMOUNT \$160	

15535 U.S. PTO
60/570666



The Invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

☒ No.

☐ Yes, the name of the U.S. Government agency and the Government contract number are:

Respectfully submitted,

James A. Mitchell Reg. No. 25 120

May 13, 2004
Date

☒ Additional inventors are being named on separately numbered sheets attached hereto.

PROVISIONAL APPLICATION FILING ONLY

WOUND DRESSING, INGREDIENT DELIVERY DEVICE AND IV HOLD-DOWN, AND
METHOD RELATING TO SAME

CLAIM OF PRIORITY

Applicant claims priority to provisional application Serial No. 60/484,711, filed July 3, 2003, and provisional patent application Serial No. 60/508,088, filed October 2, 2003.

BACKGROUND OF THE INVENTION

The present invention relates to adhesive devices used as wound dressings, ingredient delivery devices and IV hold-downs.

Wound dressing and IV hold-downs in particular comprise a layer of polymeric film having an adhesive layer on one side thereof, which is protected during storage and handling by a release liner. United States Patent Publication 2002/0107466 A1 discloses such devices which also have a handling member adhered to the non-adhesive coated side of the polymeric film by means of a pressure sensitive adhesive. The pressure sensitive adhesive used between the handle and the polymeric film is less aggressive than the pressure sensitive adhesive used on the underside of the polymeric film, such that once the polymeric film is applied to a patient's skin or mucosa, the handle can be peeled away without peeling the polymeric film away from the patient's skin.

Experience has shown that regardless of differences in adhesive strength between the skin or mucosa adhesive and the handle adhesive, there is a tendency for the edge of the polymeric film to lift away from the user's skin or mucosa when the handle member is peeled away from the back of the polymeric film. This same tendency is observed in the wound

dressings disclosed in U.S. Patent 6,169,224, where the handling member is sealed to the polymeric film by a heat activated adhesive.

SUMMARY OF THE INVENTION

In the various aspects of the present invention, inadvertent edge release caused by peeling the handle member away from the polymeric film can be minimized by the following methods or combinations thereof:

1. minimizing the electrostatic charge buildup in the localized area of the polymeric film beneath the handle, as the handle is peeled away from the film; and/or
2. decreasing the mechanical advantage of the handle relative to the thin film.

In various different preferred aspects of the invention, either or both of these are accomplished by:

1. interrupting the continuity of contact between the adhesive coated surface of the handle and the underlying non-adhesively coated surface of the polymeric film;
2. placing an anti-static ingredient in one of, the adhesive coating on the underside of the polymeric film, or in an anti-static coating on the upper or lower surface of the polymeric film itself, with the anti-static agent preferably being located in the adhesive layer on the underside of the polymeric film;

3. removing at least a portion of the periphery of the handle layer, or of the adhesive layer on the underside of the handle, so that it does not extend to the periphery of the polymeric film layer upon which the handle layer resides; and/or
4. reducing the surface area of the adhesive coating disposed on the periphery of handle.

In another aspect of the invention, an inwardly-directed thumb tab, oriented at an obtuse angle with respect to the edge of the handle in the direction in which the handle is pulled, is provided to facilitate peeling of the handle away from the polymeric film. Such a thumb tab enhances the ease with which the handle is peeled away from the polymeric film. The thumb tab starts the peeling at such an angle that the tendency of the handle to lift the underlying polymeric film away from the patient's skin or mucosa is minimized.

These and other objects, features and advantages of the invention will be more fully understood and appreciated by reference to the written specification and appended drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a plan view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with a first embodiment of the present invention;

Fig. 2 is a cross sectional view of the wound dressing, ingredient delivery device, or IV hold-down of Fig. 1, taken along line II-II of Fig 1;

Fig. 3 is a perspective view of a wound dressing, ingredient delivery device, or IV hold-down of Fig. 1, with the handle being removed;

Fig. 4 is an enlarged sectional view of a wound dressing, ingredient delivery device, or IV hold-down of Fig. 2, taken at section IV of Fig 2 with the release liner removed;

Fig. 5 is a plan view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with a second embodiment of the present invention;

Fig. 6 is a cross sectional view of a wound dressing, ingredient delivery device, or IV hold-down of Fig. 5, taken along line VI-VI, with the release liner removed;

Fig. 7 is a plan view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with a third embodiment of the present invention.

Fig. 8 is a cross sectional view of a wound dressing, ingredient delivery device, or IV hold-down of Fig. 7, taken along line VIII-VIII of Fig 7;

Fig. 9 is a plan view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with a fourth embodiment of the present invention.

Fig. 10 is a cross sectional view of a wound dressing, ingredient delivery device, or IV hold-down of Fig. 9, taken along line X-X of Fig 9;

Fig. 11 is a cross sectional view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with a fifth embodiment of the present invention;

Fig. 12 is a cross sectional view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with a sixth embodiment of the present invention;

Fig. 13 is a cross sectional view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with a seventh embodiment of the present invention;

Fig. 14 is a cross sectional of a wound dressing, ingredient delivery device, or IV hold-down in accordance with an eighth embodiment of the present invention;

Fig. 15 is a plan view of a wound dressing, ingredient delivery device, or IV hold-down of Fig. 14;

Fig. 16 is a plan view of a wound dressing, ingredient delivery device, or IV hold-down;

Fig. 17 is a cross sectional view of the wound dressing, ingredient delivery device, or IV hold-down of Fig. 16, taken along line XVII-XVII of Fig 16;

Fig. 18 is a plan view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with a tenth embodiment of the present invention; and

Fig. 19 is a plan view of a wound dressing, ingredient delivery device, or IV hold-down in accordance with an eleventh embodiment of the present invention.

BACKGROUND OF THE INVENTION

INTRODUCTION

The term "dressing" as used herein is to be understood to include wound dressings, IV hold-downs and transdermal, dermal, transmucosal and mucosal delivery systems. The various preferred embodiments disclosed herein have many components or similar components in common, which are described in this Introduction using numbers which are common to all embodiments. The differing embodiments, and the similar elements thereof, are distinguished by adding the letters a-j.

In the various preferred embodiments, the basic elements of a device in accordance with the present invention comprise a handle 10 having an adhesive coating 20 on the undersurface thereof and an inwardly-projecting thumb tab 11 (Figs. 1-3). Handle 10 is applied to the nonadhesive coated surface of a polymeric film 30 having a pressure sensitive

adhesive layer 40 on the undersurface thereof. Adhesive layer 40 is protected during handling and storage by a release liner 50 having a silicone coating layer 51. In use, release liner 50 is removed from the assembled polymeric film 30 and handle 10, and handle 10 is then used to manipulate the polymeric film and place it on the patient. Once the polymeric film has been applied to the patient, the user grasps inwardly-projecting thumb tab 11 on handle 10 and peels handle 10 away from the applied polymeric film 30.

Inadvertent edge release caused by removal of the handle 10 is minimized by any one or any combination of the following:

1. the angle at which thumb tab 11 projects from handle 10;
2. by minimizing the build up of localized electrostatic charge on the polyurethane film as the handle is removed; and/or
3. decreasing the mechanical advantage of handle 10 relative to film 30.

Objects 2 and 3 are accomplished by any one or any combination of the following:

1. interrupting the continuity of contact between the adhesive coated surface of the handle and the underlying non-adhesively coated surface of the polymeric film;
2. placing an anti-static ingredient in one of, the adhesive coating on the underside of the polymeric film, or in an anti-static coating on the upper or lower surface of the polymeric film itself, with the anti-static agent preferably being located in the adhesive layer on the underside of the polymeric film;

3. removing at least a portion of the periphery of the handle layer, or of the adhesive layer on the underside of the handle, so that it does not extend to the periphery of the polymeric film layer upon which the handle layer resides; and/or
4. reducing the surface area of the adhesive coating disposed on the periphery of handle.

Handle 10 is preferably made of a stiffer and generally thicker material than that of polymeric film 30. Typical of such materials are plastic or paper material. Useable plastics include polyesters, polycarbonates, PVC's, polyurethanes, polyethylene vinyl acetates, polyester copolymers, polyethylenes, and polypropylenes. In the preferred embodiment a silicone coated paper 50, with a silicone coating 51 on the upper surface thereof, is used.

The undersurface of each handle 10 is coated with an adhesive 20, preferably a pressure sensitive adhesive (Fig. 2), which is moderately aggressive with respect to polymeric film 30, but which does not adhere or adheres less aggressively to either the silicone coating 51 on release liner 50 or to human skin. In this way, a user can readily fold back an end portion of release liner 50 to expose an end of handle 10, and the exposed end can then be used to peel film 30 away from release liner 50. The adhesive of layer 20 is "moderately aggressive" in that handle 20 remains attached to polymeric film 30 when it is peeled away from release liner 50, and while it is being handled and applied to the patient's skin. However, adhesive 20 is less aggressive with respect to its adhesion to polymeric film 30, than is the adhesion of layer 40 on the undersurface of polymeric film 30 toward human skin or mucosa. As a result, handle 10 can be peeled away from polymeric film 30, once film 30 is applied to the patient.

One type of adhesive which we have found useful for layer 20 on the undersurface of handle 10 is a low tack removable acrylate-based adhesive with a peel adhesive level of approximately three ounces. Other useful adhesives include, but are not limited to, silicone, urethane, synthetic rubber and natural rubber. Adhesives of this type can be formulated to have essentially no or very little adhesion to the human skin or to the silicone coating 51 on the release liner 50, but still adhere firmly but releasably to film 30.

Polymeric film 30 is preferably comprised of any breathable and waterproof material. In the preferred embodiment, a polymeric film on the order of from about 0.5 to about 4 mils (0.0005 to 0.004 inches) is preferred. The film is preferably very flexible, allowing it to conform readily to the user's skin or mucosa. The film must have sufficient strength to afford resistance to damage in handling and in use. It also preferably allows the passage of oxygen, thereby allowing the skin or mucosa to breathe. The polymeric film material preferably is a polyurethane film such as a Pebax® film (MediFilm 810, 2 mils, Mylan). Additionally, copolymers of polyethylene and vinyl acetate are also preferable.

The adhesive layer 40 may be any adhesive that bonds well to skin or mucosa. Preferably, a pressure sensitive adhesive is used. A type of adhesive found useful for adhesive layer 40 is a permanent acrylate-based pressure sensitive adhesive designed for skin, with a peel adhesion level of approximately 50 ounces. Other useful adhesives include, but are not limited to, silicone, urethane, synthetic rubber and natural rubber. Such adhesives can be formulated to adhere releasably to the silicone coated surface 51 of a release liner 50. At the same time, they can be formulated to adhere firmly to the patients skin or mucosa such that polymeric film 30 will not peel away unless someone intends to do so. For example, one can

use an acrylate derivative adhesive such as copolymers of alkyl acrylate/vinyl acetate containing -OH or/and -COOH functional groups, or hydrophobic styrenic rubber polymer or PIB containing 1 to 20% hydroattractants such as PVP, PVA, and cellulose derivatives such as Duro-Tak 87-2516 (National Starch), and PIB containing 20% Kollidon® CL-M (BASF)..

The entire assembly of handle 10, adhesive layer 20, polymeric film 30 and adhesive layer 40 is releasably adhered to a release liner 50. Release liner 50 may be comprised of any material that will releasably adhere adhesive layer 40. However, in the preferred embodiment, release liner 50 is a paper material with a silicone coating 51 on the top surface thereof.

The very properties of polymeric film 30 which make it desirable in use make it difficult to handle in application. The drape and flexibility properties of polymeric film 30 may cause it to fold over onto itself and self-adhere relatively easily when one is trying to apply the system to the user's skin. The thicker handle 10 disclosed in the preferred embodiment reduces these shortcomings and makes the systems relatively easy to apply without fouling polymeric film 30. However, the structural characteristics of the stiffer and generally thicker material of handle 10 which aid in the application is compromised when a cut line 13 is made to handle 10 (Fig. 1). Cut line 13, which aids the applicator in the removal of handle 10, compromises the structural integrity of handle 10 and allows the polymeric film 30 to fold over and adhere to itself.

Edge release typically occurs with these systems when handle 10 is removed from polymeric film layer 30. The generally thicker material of handle 10 creates a lever arm out of handle 10 when handle 10 is being peeled off of film 30. This lever arm created by handle 10 acts to pry up film 30 from the patient's skin. If this force is great enough the edge of film 30

can separate from the patient's skin (e.g., edge release occurs). In general, as the stiffness of the material of handle 10 increases, the less flexible it becomes. The less flexible the handle becomes, the longer the lever arm becomes and this in turn creates higher forces which act upon film layer 30 causing more significant edge release. In addition, it is believed that as handle 10 is removed from polymeric film layer 30, it causes an electrostatic buildup in film layer 30, which contributes to the tendency of the edge of film 30 to release from and be pulled away from a patient's skin or mucosa. Therefore, the properties that make handle 30 useful, namely its stiffness, also create edge release.

THE ANGLED THUMB TAB

Tab 11 is provided on handle 10 to minimize the tendency of film 30 to fold over at cut line 13, as well as aid in the removal of handle 10. Inwardly-projecting thumb tab 11 includes a distal portion 12. Preferably, the underside of thumb tab 11 is not coated with adhesive. In the preferred embodiment, the leading edge A of thumb tab 11 is disposed at an angle greater than 90 degrees with respect to the edge of the handle in the direction "B" in which the handle is pulled, and distal portion 12 extends beyond cut line 13 into window 15 of handle 10. Preferably, the angle is between about 120° and about 150°, and most preferably about 135°. This placement of distal portion 12 provides more support for polymeric film 30 and handle 10 and it is therefore less likely that polymeric film 30 will fold at cut line 13. However, this is merely the preferred embodiment and tab 10 may also be disposed outwardly. Similarly, it is preferably that cut line 13 extends between the edges of handle 10 at between about 130° and about 150°, most preferably about 135°, with respect to the direction in which handle 10 will

be initially peeled away from film 30. This also helps prevent film 30 from buckling across the cut through the handle.

As described above, edge release typically occurs with these systems when handle 10 is removed from polymeric film layer 30. Tab 11 minimizes this tendency by reducing the mechanical advantage that handle 10 has over polymeric film 30 when handle 10 is being peeled off. The mechanical advantage is reduced by the angle at which thumb tab 11 projects from handle 10 and subsequently, the angle at which handle 10 is removed from polymeric film 30.

INTERRUPTING THE CONTINUITY OF CONTACT BETWEEN THE HANDLE AND THE POLYMERIC FILM

In addition to the mechanical advantages of thumb tab 11, edge release can also be minimized by interrupting the continuity of contact between the adhesive coated surface of handle 10 and the underlying non-adhesively coated surface of the polymeric film 30, at least in the vicinity of at least a portion of the edge of handle 10. Although not wishing to be bound by theory, it is believed that this interruption helps to minimize edge release in three ways:

1. less contact area means handle 10 can be removed more easily;
2. the mechanical advantage of the handle relative to the film 30 edge is reduced; and
3. localized electrostatic build up when handle 10 is peeled away from film 30 is reduced.

Interrupting the contact between the adhesive layer 20 of handle 10 and film 30 reduces the contact area. We have found it helpful to reduce the contact area by from about 10% to about 70%, preferably about 10% to about 50%, and most preferably from about 10% to about

30%, as compared to the contact area without such interruptions in continuity. If a greater reduction in contact area is desired, a more aggressive adhesive can be used in adhesive layer 20.

One technique for interrupting the adhesive layer of the handle and the non-adhesively coated surface of polymeric film 30 is to texture handle 10, at least at adhesive layer 20 on handle 10 which faces and is adhered to polymeric film 30. Preferably, this texturing is done by piercing slots 16 through handle 10 and adhesive coating layer 20 (Figs. 1-6). Other techniques include placing pin holes through handle 10 (Figs. 7, 8); knurling handle 10 (Figs. 9, 10); embossing or debossing handle 10; printing adhesive layer 20 in a pattern (Fig. 11); and employing a handle material having a relatively rough surface facing polymeric film layer 30. Alternatively, the polymeric film 30 may be textured on the side facing handle 10 (Fig. 12). Preferably, the texturing is done in such a way as to break the adhesive coating layer itself, as distinguished from merely making it irregular in shape (see e.g., Figs. 2, 4 and 8).

As depicted in Fig. 1, a first embodiment is shown utilizing a plurality of piercing slots 16 completely surrounding and angularly disposed with respect to window 15. The slots 16 may be pierced from the either side. However, in the preferred embodiment the slots are pierced from the top surface and through adhesive layer 20 on handle 10 as shown in Fig. 2.

In response to the piercing action, material of handle 10 at the pierced location is deflected toward polymeric film layer 30 resulting in a raised portion 17 of slot 16 (Fig. 2). Film 30 tends to bridge over raised portions 17 of slots 16, creating a "tunnel" at which film 30 is separated from handle 10. Raised portion 17 thereby effectively reduces the area of

contact between film 30 and adhesive layer 20 of handle 10. This reduces the adhesive retention of handle 10 to polymeric film 30.

Also when handle 10 is removed from polymeric film 30 an atmospheric venting effect 21 occurs in the tunneling area (Fig. 4). This venting effect enhances the ease of removal of the handle. The result is less inadvertent edge release.

Additionally, raised portion 17 which is in contact with polymeric film 30 provides a conductive pathway between polymeric film 30 and handle 10. This pathway interrupts the continuity of contact between the adhesive coated surface 20 of handle 10 and the underlying non-adhesively coated surface of polymeric film 30 thereby minimizing the electrostatic buildup of localized electrostatic charge on the polyurethane film during the removal of handle 10. This minimization of electrostatic build up contributes towards the reduction in edge release.

Fig. 5 shows a second embodiment including slots 16a which are parallel to window 15a along its sides, and angularly disposed with respect to the top and bottom surface. In this configuration, after the release liner 50a is removed, atmospheric venting effect 21a again occurs (Fig. 6).

A third embodiment is shown in Fig. 7 and is similar to the first two embodiments except that it utilizes a puncture or pinhole to interrupt the continuity between the handle 10b and the polymeric film 30b. As shown in Fig. 8, pinholes 16b minimize edge release by reducing the adhesion of handle 10b to the polymeric film 30b and also providing a conductive pathway between polymeric film 30 and handle 10 in order to minimize electrostatic buildup as described above.

A fourth embodiment using a knurled pattern is depicted in Fig. 9. The knurled pattern may take any geometrical shape and be either embossed or debossed on handle 10c. Additionally, the pattern may be varied thereby increasing or decreasing the contact area to accommodate the application requirements. Unique to this embodiment is the feature that the knurls 16c do not puncture handle 10c. Instead, the reduction in adhesion is accomplished through the bottom of knurls 16c residing directly on polymeric film layer 30c and therefore reducing the adhesive contact surface of polymeric film 30c, as shown in Fig. 10. However, this is not meant to be limiting and knurls 16c may puncture handle 10c if required. Embossing or debossing handles 10 is similar to knurling, though the raised portion would probably be larger in area than the knurl projections.

Additionally, a fifth embodiment is shown in Fig. 11. This embodiment reduces the adhesion between handle 10d and polymeric film layer 30d by patterning the adhesive layer. As described above, the pattern may be varied thereby increasing or decreasing the contact area according to the specific requirements of the application.

Still further, it is possible to accomplish this reduction in continuity through the use of a rough surface on handle 10, facing polymeric film layer 30. This can be done, for example, through the use of a rough or non smooth paper for handle 10.

Fig. 12 shows a sixth embodiment which uses a polymeric film layer 30e having at least a textured upper surface to reduce the continuity of contact between handle 10e and polymeric film 30e. The pattern may take any geometrical shape and be either embossed or debossed on polymeric film layer 30e. Additionally, as described above, the pattern may be varied thereby increasing or decreasing the contact area to accommodate the application

requirements. The patterning of polymeric film layer 30e may be accomplished mechanically or chemically.

While the embodiments described above are wound dressings or IV hold-down devices, the various aspects of the present invention are also applicable to devices designed to deliver active ingredients to or through the dermal or mucosal layers. Such delivery systems typically deliver the active via a gel modulated system, membrane modulated system, or an adhesive modulated system. All of the embodiments of Figs. 1-19 can be made to be ingredient delivery devices by incorporating an active ingredient into adhesive layer 40-40j, for example.

The delivery system depicted in Fig. 14 includes a breathable and waterproof polymeric film 30g. Layered to a first side of film 30g is adhesive layer 40g. Adhered to adhesive layer 40g of film 30g is an active ingredient containing island 60g. Island 60g comprises a thin or ultra thin polymeric backing film 62g. Layered to backing film 62g is an active ingredient layer 63g that may or may not be incorporated into an adhesive.

INCORPORATING AN ANTI-STATIC INGREDIENT

Edge release can also be minimized by utilizing an anti-static coating to minimize the electrostatic buildup that occurs when handle 10 is removed. A seventh embodiment using an anti-static coating 61 is shown in Fig. 13. The anti-static coating layer 61 on polymeric film layer 30f acts to minimize the electrostatic buildup of localized electrostatic charge on polyurethane film 30f during the removal of the handle 10f. The minimization of electrostatic build up contributes towards the reduction in edge release. Alternatively, or in addition, anti-static material may be incorporated onto the lower surface of polyurethane film 30f or into adhesive layer 40f of polyurethane film 30f.

REMOVING A PORTION OF HANDLE OR ADHESIVE AT THE PERIPHERY

Removing a portion of handle 10, or its underlying adhesive layer 20, from over at least a portion of the edge area of film layer 30 helps to minimize edge release. Although not wishing to be bound by theory, it is believed that this is accomplished in three ways:

1. less adhesive contact area means handle 10 can be removed more easily;
2. reducing the ability of handle 10 to act as a lifting lever relative to film 30, at least when a portion of the handle per se is removed; and
3. minimizing the localized electrostatic build up at the periphery of film 30 when handle 10 is peeled from film 30, by moving the periphery of handle 30 away from the edge of film 30.

One way to move at least a portion of the edge of said handle away from the periphery of said polymeric film is to pattern the handle layer with a scalloped pattern as shown in Figs. 16 and 17. In this embodiment, the scalloping extends around the entire perimeter of handle 10. The scalloped edge reduces the mechanical advantage of handle 10 primarily in two ways. The first is by reducing the surface area of adhesive coating 20 disposed on the periphery of handle 10, and the second is by reducing the ability of handle 10 to act as a lever. In the first mode, a portion of the periphery of handle 10 is removed resulting in scalloped edge 15. Simultaneous to this removal of a portion of handle 10 is the removal of a corresponding portion of adhesive coating 20 attached thereto. This removal of adhesive 20 on the periphery of handle 10 reduces the upward force exerted on the periphery of polymeric film 30 by adhesive coating 20 during its removal. Reducing the upward force exerted on the periphery

of polymeric film 30 reduces edge lift. In the second mode, scalloped edge 15 reduces the ability of the generally thicker material of handle 10 to act as a lever arm.

When the peripheral interaction between adhesive layer 20 and polymeric film 30 is removed, the localized electrostatic buildup on film 30 is also reduced. This is because the interaction between adhesive layer 20 and film layer 30, during their separation, causes the electrostatic buildup. The removal of a portion of the peripheral edge of handle 10, and subsequently adhesive layer 20, or the removal of some of the adhesive at the edges of handle 10 minimizes the electrostatic buildup on the peripheral edge of polymeric film 30 by removing this interaction and therefore, reduces edge lift.

The scalloped edge (15) of handle 10 is depicted in Fig. 16 as having a wave like or sinusoidal like pattern, leaving projecting portions 16 extending to the edge of film layer 30. Other geometrical forms may be used which reduce the interaction between the periphery of handle 10 and the periphery of film 30. While a handle could be made that simply does not extend to the edge of film layer 30, thereby reducing edge lift, the scalloped pattern has the advantage of having end portions 16 that extend to the edge of film 30. End portions 16 act to support thin film 30 and keep it from folding over onto itself during application. Therefore, scalloped edge 15 retains the benefits of a handle layer (e.g., ease of application) while minimizing the negative effects of a handle layer (e.g., edge lift).

In the Fig. 18 embodiment, the edge portion of handle 10 along two opposite sides thereof, preferably the longest sides, have been substantially removed as a continuous, uninterrupted strip. This leaves the longest edge portions 31 of polymeric film but retains a portion of handle 10 along two other sides which extends to the film periphery sides to support

film 30 during application. Preferably, only the central portion of the edge of handle 10 is removed, such that end or corner portions 11 of handle 10 extend out to the edges or corners to give stability. The Fig. 19 embodiment is similar to the Fig. 18 version, but also incorporates a window of removed handle material which is centrally located on the dressing, leaving the central portion 32 of film 30 also exposed.

Although only a few preferred embodiments have been shown and described it is envisioned that there are numerous geometrical patterns that may be used. Additionally, there are supplementary methods which can be combined with the various edge geometries for reducing the edge lift even further. For example, the preferred embodiment may include additional features such as texturing handle 10, texturing adhesive layer 20, texturing polymeric film layer 30 and/or using an anti-static ingredient in one of, the adhesive coating on the underside of the polymeric film, or on the upper or lower surface of the polymeric film itself. Additionally, texturing may be done by piercing slots, placing pin holes, knurling, embossing or debossing, or creating a relatively rough surface on handle 10.

CONCLUSION

The embodiments described above minimize the problem of edge release which typically occurs in adhesive devices used as wound dressings, ingredient delivery devices and IV hold-downs. Of course it is understood that the above are preferred embodiments only, and that various changes and alterations can be made without departing from the spirit and scope of the invention as set forth in the appended claims, as interpreted in accordance with the principles of patent law.

The invention claimed is:

1. A wound dressing, ingredient delivery device or IV hold-down comprising:
 - a handle having a first side;
 - a first adhesive layer on at least a portion of said first side of said handle;
 - a polymeric film having a first and second side, at least a portion of said first side of said polymeric film being coated with a second adhesive layer;
 - said handle being adhered to said second side of said polymeric film by said first adhesive layer, the continuity of contact between said adhesive coated surface of said handle and the underlying second surface of said polymeric film being interrupted at least in the vicinity of at least a portion of the edge of said handle.
2. The device of claim 1 in which said continuity is interrupted to such an extent that the contact area between said handle and said polymeric film is reduced by from about 10% to about 70%.
3. The device of claim 1 in which said continuity is interrupted to such an extent that the contact area between said handle and said polymeric film is reduced by from about 10% to about 50%.
4. The device of claim 1 in which said continuity is interrupted to such an extent that the contact area between said handle and said polymeric film is reduced by from about 10% to about 30%.

5. The device of claim 2 in which said continuity is interrupted by said handle being textured.
6. The device of claim 5 in which said texturing is accomplished by piercing said handle and said first adhesive coating.
7. The device of claim 6 in which said piercing is conducted by piercing slots through said handle and said first adhesive layer.
8. The device of claim 7 in which said slots are oriented diagonally relative to the edge of said handle.
9. The device of claim 7 in which said slots are oriented generally parallel to the edge of said handle.
10. The device of claim 6 in which said piercing is conducted by piercing pinholes through said handle and said first adhesive layer.
11. The device of claim 5 in which said texturing comprises said handle being knurled.

12. The device of claim 5 in which said texturing comprises said handle being embossed or debossed.

13. The device of claim 5 in which texturing comprises said first adhesive coating being printed in a pattern on said first side of said handle.

14. The device of claim 5 in which said texturing comprises said handle being made of a material having a relatively rough first surface facing said polymeric film.

15. The device of claim 2 in which said interruption of the continuity of contact between said handle and said polymeric film is accomplished by said second side of said polymeric film being textured.

16. The device of claim 2 in which said interruption of the continuity of contact between said handle and said polymeric film is accomplished by said handle and said first adhesive coating being pierced with slots, said slots being generally diagonally relative to the perimeter of said handle.

17. The device of claim 2 in which said said interruption of the continuity of contact between said handle and said polymeric film is accomplished by said handle and said first adhesive coating being pierced with slots, said slots being generally parallel relative to the perimeter of said handle.

18. A wound dressing, ingredient delivery device or IV hold-down comprising:

a handle having a first side;

a first adhesive layer on at least a portion of said first side of said handle;

a polymeric film having a first and second side, at least a portion of said first side of said polymeric film being coated with a second adhesive layer;

said handle being adhered to said second side of said polymeric film by said first adhesive layer;

an anti-static ingredient being incorporated into one of said second adhesive coating on said first side of said polymeric film, or into an anti-static coating on either said first or second surface of said polymeric film.

19. The device of claim 18 in which said anti-static ingredient is incorporated into said second adhesive coating on said first side of said polymeric film.

20. A wound dressing, ingredient delivery device or IV hold-down comprising:

a handle having a first side;

a first adhesive layer on at least a portion of said first side of said handle;

a polymeric film including a first and second side;

at least a portion of the first side of said polymeric film being coated with a second adhesive layer;

said handle being adhered to said second side of said polymeric film by said first adhesive layer;

said handle including a thumb tab having a first surface corresponding to said first surface of said handle, said first surface of said thumb tab being free of adhesive coating, said thumb tab projecting away from an edge of said handle, said thumb tab having a leading edge extending away from said handle at an angle greater than 90° with respect to the edge of said handle in the direction in which the handle is lifted and pulled when peeling said handle away from said polymeric film.

21. The device of claim 20 in which said angle is between about 120° and about 150° .

22. The device of claim 20 in which said angle is about 135° .

23. The device of claim 20 in which said handle is configured in the shape of a frame, such that it has an exterior perimeter edge and an interior perimeter edge, said interior perimeter edge defining an opening in said handle;

said handle frame including a diagonal cut extending between said inner and outer perimeter edges of said handle, generally in alignment with said leading edge of said thumb tab.

24. The device of claim 20 in which said diagonal cut and said leading edge of said thumb tab are oriented at an angle of between about 120° and about 150° relative to said edge of said

handle in the direction in which said handle is to be pulled and lifted away from said polymeric film.

25. The device of claim 20 in which said diagonal cut and said leading edge of said thumb tab are oriented at an angle of about 135° relative to said edge of said handle in the direction in which said handle is to be pulled and lifted away from said polymeric film.

26. The device of claim 20 in which said thumb tab projects inwardly from said interior edge of said handle.

27. The device of claim 26 in which said diagonal cut and said leading edge of said thumb tab are oriented at an angle of between about 120° and about 150° relative to said edge of said handle in the direction in which said handle is to be pulled and lifted away from said polymeric film.

28. The device of claim 26 in which said diagonal cut and said leading edge of said thumb tab are oriented at an angle of about 135° relative to said edge of said handle in the direction in which said handle is to be pulled and lifted away from said polymeric film.

29. A wound dressing, ingredient delivery device or IV hold-down comprising:
a handle having a first side and a periphery;
a first adhesive layer coating at least a portion of said first side of said handle;

a polymeric film layer including a first side, a second side and a periphery;

a second adhesive layer coating at least a portion of said first side of said polymeric film layer, said handle being adhered to said second side of the polymeric film layer via said first adhesive layer;

wherein a portion of the periphery of one of said handle, including said first adhesive layer, or a portion only of said first adhesive layer, does not extend to said periphery of said polymeric film layer.

30. The device according to claim 29 wherein:

the periphery of one of said handle or said first adhesive layer is fashioned in a repeating pattern with only a portion of each repeated pattern extending to said periphery of said polymeric film layer.

31. The device according to claim 30 wherein:

the shape of said repeating pattern is scalloped.

32. The device according to claim 30 wherein:

at least a continuous substantial portion of at least one of a plurality of sides of the periphery of one of said handle or said first adhesive layer does not extend to the periphery of said polymeric film layer.

33. The device of claim 32 in which said continuous substantial edge portion is centrally located between the ends of said side such that the end portions of said side extend to said periphery of said polymeric film to give stability to the corners thereof.
34. The device according to claim 32 wherein:
said handle further includes a central opening.
35. The device according to claim 29 wherein at least a continuous, substantial portion of at least two opposite sides of the periphery of one of said handle or said first adhesive layer does not extend to the periphery of the corresponding opposite sides of said polymeric film layer.
36. The device of claim 35 in which said continuous substantial edge portions are centrally located between the ends of said opposite sides such that the end portions of said sides extend to said periphery of said polymeric film to give stability to the corners thereof.
37. The device according to claim 36 wherein:
said handle further includes a central opening.
38. A wound dressing, ingredient delivery device or IV hold-down comprising:
a handle having a first side;
a first adhesive layer on at least a portion of said first side of said handle and means for minimizing the localized electrostatic charge buildup on said polymeric film as said handle is peeled away from said film when it is applied to a patient's skin or mucosa, thereby minimizing edge release of said polymeric film from said patient's skin or mucosa.

39. A method of minimizing edge release in wound dressings, ingredient delivery devices and IV hold-downs which incorporate a handle member to assist in their application, wherein the removal of said handle member after application tends to lift the edge of the adhesive coated polymeric film of the dressing or device away from the skin or mucosa of the patient, said method comprising:

providing a handle having a first side;

coating at least a portion of the first side of said handle with a first adhesive layer;

providing a polymeric film including a first and a second side;

coating at least a portion of the first side of the polymeric film with a second adhesive layer, said handle being adhered to said second side of the polymeric film by said first adhesive layer; and

minimizing the localized electrostatic charge buildup on said polymeric film as the handle is peeled away from applied film, thereby minimizing edge release of said film from the patient's skin or mucosa.

40. A method of minimizing edge release in wound dressings, ingredient delivery devices and IV hold-downs which incorporate a handle member to assist in their application, wherein the removal of said handle member after application tends to lift the edge of the adhesive coated polymeric film of the dressing or device away from the mucosa of the patient, said method comprising:

providing a handle having a first side;

coating at least a portion of the first side of said handle with a first adhesive layer;

providing a polymeric film including a first and second side;

coating at least a portion of the first side of said polymeric film with a second adhesive layer, said handle being adhered to said second side of said polymeric film by said first adhesive layer; and

interrupting the continuity of contact between said first adhesive layer and said polymeric film, thereby minimizing edge release of said film from the patient's skin or mucosa.

41. A method of minimizing edge release in wound dressings, ingredient delivery devices and IV hold-downs which incorporate a handle member to assist in their application, wherein the removal of said handle member after application tends to lift the edge of the adhesive coated polymeric film of the dressing or device away from the mucosa of the patient, said method comprising:

providing a handle having a first side;

coating at least a portion of the first side of said handle with a first adhesive layer;

providing a polymeric film including a first and second side;

coating at least a portion of the first side of said polymeric film with a second adhesive layer, said handle being adhered to said second side of said polymeric film by said first adhesive layer; and

reducing the area of contact between said first adhesive coating and said polymeric film by from about 10 to about 70%.

42. A method of minimizing edge release in wound dressings, ingredient delivery devices and IV hold-downs which incorporate a handle member to assist in their application, wherein the removal of said handle member after application tends to lift the edge of the adhesive coated polymeric film of the dressing or device away from the mucosa of the patient, said method comprising:

providing a handle having a first side;

coating at least a portion of the first side of said handle with a first adhesive layer;

providing a polymeric film including a first and second side;

coating at least a portion of the first side of said polymeric film with a second adhesive layer, said handle being adhered to said second side of said polymeric film by said first adhesive layer; and

providing said handle with a thumb tab which is not adhesively coated on its said first surface, said thumb tab projecting away from an edge of said handle at an angle greater than 90° with respect to the edge of said handle in the direction in which the handle is lifted and pulled in a peeling away motion for peeling said handle away from said polymeric film.

43. A method of minimizing edge release in wound dressings, ingredient delivery devices and IV hold-downs which incorporate a handle layer to assist in their application, wherein the removal of the handle layer, after application of the device to the patient, initiates the edge release, said method comprising:

providing a handle having a first side and a periphery;

applying a first adhesive layer on at least a portion of said first side of said handle;

providing a polymeric film layer including a first side, a second side and a periphery;

applying a second adhesive layer to at least a portion of said first side of the polymeric film layer, said handle being adhered to said second side of the polymeric film layer via said first adhesive layer;

configuring one of said handle, including said first adhesive layer, or said first adhesive layer itself, such that only a portion of the periphery of said handle or said first adhesive layer extends to the periphery of the polymeric film layer, leaving a portion of said periphery of said handle recessed away from said periphery of said polymeric film layer.

**WOUND DRESSING, INGREDIENT DELIVERY DEVICE AND IV HOLD-DOWN, AND
METHOD RELATING TO SAME**

ABSTRACT

An adhesive device used as a wound dressing, ingredient delivery device or IV hold-down in which inadvertent edge release of these devices along the periphery of the polymeric film layer is minimized when the handling layer, which is adhered to the polymeric film layer, is removed after application of the polymeric film layer to the patient.




FIG. 3




FIG. 1




FIG. 2




FIG. 5




FIG. 4




FIG. 6




FIG. 8




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 7




FIG. 9




FIG. 14




FIG. 16




FIG. 15




FIG. 17




FIG. 19




FIG. 18